Telecommunications Authority of Trinidad and Tobago



Consultative Document

on the

Spectrum Plan for the Accommodation of Public Mobile Telecommunications Services

(First of two rounds)

(Version 4.1)

Maintenance History			
Date Change Details			
1 st August 2004	Approved version	1.0	
30 th September 2008	Final approved version – Plan updated based on the conclusion of the competitive licensing process for the introduction of new public mobile telecommunications service concessionaires, which concluded in June 2005	2.0	
26 th June 2013	Final approved version – Plan updated following consultation, to include 700 MHz spectrum for the provision of public mobile telecommunications services	3.0	
15 th November 2017	Final approved version – Plan updated based on consultation, to include AWS Band and to change from the US 700 MHz band plan to the APT 700 MHz band plan for the provision of public mobile telecommunications services	4.0	
1 st March 2023	Consultative document including the shift in the PPDR allocation in the 700 MHz band; the amendment of the frequency assignment plan for the 850 MHz band; the expansion of the 1900 MHz and 1.7/2.1 GHz bands; the inclusion of 2.5 and lower 3.5 GHz bands for cellular mobile radiocommunications service; and revisions to the existing spectrum caps	4.1	

© Telecommunications Authority of Trinidad and Tobago 2023

All rights reserved. No part of this publication may be reproduced or transmitted in any form or by any means or stored in any retrieval system of any nature without the prior written permission of the Telecommunications Authority of Trinidad and Tobago, except for permitted fair dealing under the Copyright Act of Trinidad and Tobago Chapter 82:80 or in accordance with any permission granted by the Authority in respect of photocopying and/or reprographic reproduction. Full acknowledgement of author and source must be given when citing this publication.

This document may be cited as: Telecommunications Authority of Trinidad and Tobago (TATT 2023). *Consultative Document on the Spectrum Plan for the Accommodation of Public Mobile Telecommunications Services (March 2023).* Barataria, Trinidad and Tobago.

Table of Contents

1	Intro	duction	1
	1.1	Background	1
	1.2	Purpose	2
	1.3	Objectives	2
	1.4	Scope	2
	1.5	Relevant Legislation	3
	1.6	Other Relevant Documents	4
	1.7	Review Cycle	5
	1.8	Consultation Process	5
	1.9	Definitions	5
2	Cons	siderations for the Accommodation of Public Mobile Telecommunications Services	7
	2.1	Global Environment	7
	2.2	National Considerations	.10
3	Freq	uency Assignment Principles	.14
4	Freq	uency Assignment Plans for Public Mobile Telecommunications Services	.15
	4.1	The 700 MHz Band (703–748/758–803 MHz)	.15
	4.1.1	Selection of Frequency Assignment Plan	.15
	4.1.2	P. Frequency Assignment Plan	.17
	4.1.3	B Licensing Process and Conditions	.18
	4.1.4	Technical Operating Conditions and Specifications	. 19
	4.2	The 850 MHz Band (824–849/869–894 MHz)	.20
	4.2.1	Selection of Frequency Assignment Plan	.20
	4.2.2	P. Frequency Assignment Plan	. 20
	4.2.3	B Licensing Process and Conditions	.21
	4.2.4	Technical Operating Conditions and Specifications	.22
	4.3	The 1900 MHz Band (1850–1915/1930–1995 MHz)	.23
	4.3.1	Selection of a Frequency Assignment Plan	.23
	4.3.2	P. Frequency Assignment Plan	.23
	4.3.3	Licensing Process and Conditions	.24
	4.3.4	Technical Operating Conditions and Specifications	.24
	4.4	The 1.7/2.1 GHz Band (1710–1780/2110–2180 MHz)	.26
	4.4.1	Selection of Frequency Assignment Plan	.26
	4.4.2	P. Frequency Assignment Plan	.26
	4.4.3	Licensing Process and Conditions	.27
	4.4.4	Technical Operating Conditions and Specifications	. 28
	4.5	The 2.5 GHz Band (2496–2690 MHz)	. 29
	4.5.1	Selection of Frequency Assignment Plan	. 29
	4.5.2	P. Frequency Assignment Plan	. 30
	4.5.3	B Licensing Process and Conditions	.31
	4.5.4	Technical Operating Conditions and Specifications	. 31
	4.6	The Lower 3.5 GHz Band (3300–3800 MHz)	.33
	4.6.1	Selection of Frequency Assignment Plan	.33

4.6.2	Frequency Assignment Plan	
4.6.3	Licensing Process and Conditions	
4.6.4	Technical Operating Conditions and Specifications	
References		

List of Figures

Figure 1: Cellular Mobile Frequency Bands (low-band and mid-band spectrum)	9
Figure 2: 700 MHz Band Plans	16
Figure 3 2.5 GHz Band Plans	

List of Tables

Table 1: Frequency Bands Identified for IMT (Source: ITU-R Radio Regulations	Resolutions and
Recommendations Edition of 2020)	8
Table 2: Frequency Allocations for 2G, 3G, 4G and 5G Cellular Mobile Networks	
Table 3: Frequency Assignment Plan for 700 MHz Band	17
Table 4: Maximum Technical Operating Specifications for the 700 MHz Band	19
Table 5: Frequency Assignment Plan for 850 MHz Band	
Table 6: Maximum Technical Operating Specifications for the 850 MHz Band	
Table 7: Frequency Assignment Plan for 1900 MHz Band	
Table 8: Maximum Technical Operating Specifications for the 1900 MHz Band	
Table 9: Frequency Assignment Plan for the AWS Band	
Table 10: Maximum Technical Operating Specifications for the AWS Band	
Table 11 Frequency Assignment Plan for 2.5 GHz Band	
Table 12: Maximum Technical Operating Specifications for the 2.5 GHz Band	
Table 13: Frequency Assignment Plan for the Lower 3.5 GHz Band	
Table 14: Maximum Technical Operating Specifications for the Lower 3.5 GHz Band	

Abbreviations

2G	second generation
3G	third generation
3GPP	3rd Generation Partnership Project
4G	fourth generation
5G	fifth generation

APT	Asia-Pacific Telecommunity
AWS	advanced wireless services
BPSK	binary phase-shift keying
BWA	broadband wireless access
CDMA	Code-Division Multiple Access
CEPT	European Conference of Postal and Telecommunications Administrations
EDGE	Enhanced Data Rates for GSM Evolution
EIRP	equivalent isotropically radiated power
ERP	effective radiated power
FDD	frequency division duplexing
GHz	gigahertz
GSM	Global System for Mobile communications
GPRS	General Packet Radio Service
HSPA	High Speed Packet Access
HSPA+	Evolved High Speed Packet Access
ICT	information and communications technology
IMT	International Mobile Telecommunications
ITU	International Telecommunication Union
ITU-R	International Telecommunication Union Radiocommunications
kHz	kilohertz
LTE	Long-Term Evolution
LTE-A	LTE Advanced
MHz	megahertz
NSP	National Spectrum Plan
PCS	personal communications services
PMTS	public mobile telecommunications services
PPDR	public protection and disaster relief
QPSK	quadrature-phase shift keying
SPTWG	Spectrum Planning Technical Working Group
TATT	Telecommunications Authority of Trinidad and Tobago
TDD	time division duplexing
UMTS	Universal Mobile Telecommunications System
WCDMA	Wideband Code Division Multiple Access
WRC-07	World Radiocommunication Conference 2007
WRC-15	World Radiocommunication Conference 2015

1 Introduction

1.1 Background

The Telecommunications Authority of Trinidad and Tobago (the Authority) is mandated by the Telecommunications Act, Chap. 47:31 (the Act) under section 41(1) to:

regulate the use of the spectrum in order to promote the economic and orderly utilisation of frequencies for the operation of all means of telecommunications and to recover the cost incurred in the management of the spectrum.

To facilitate the introduction of additional cellular mobile operators, the Authority allocated in 2004 spectrum in the 850 MHz and 1900 MHz bands based on prevailing cellular mobile technologies. Concessions were consequently granted by the Minister to two operators to provide public telecommunications services and operate public domestic mobile telecommunications networks, and the incumbent and both entrants were assigned spectrum in these bands.

Pursuant to the Authority's commitment to consider additional bands for International Mobile Telecommunications (IMT), in 2017, the Authority revised its *Spectrum Plan for Public Mobile Telecommunications Services (June 2013)* to include the advanced wireless services (AWS) band comprising 1.7/2.1 GHz spectrum and the 700 MHz band, adopting the Asia-Pacific Telecommunity (APT) channel plan. In April 2019 and June 2020, the Authority invited the existing cellular mobile operators to apply for 1.7/2.1 GHz and 700 MHz spectrum, which resulted in assignments in both bands.

The cellular mobile sector currently comprises two operators – Digicel (Trinidad & Tobago) Limited and Telecommunications Services of Trinidad and Tobago Limited (TSTT). These operators have deployed Global System for Mobile communications (GSM) and its enhancements, Wideband Code Division Multiple Access (WCDMA) with Evolved High-Speed Packet Access (HSPA+) and Long-Term Evolution (LTE) technologies within the spectrum assigned.

In keeping with the principles of the *Spectrum Management Framework (October 2022)* to allocate spectrum to the highest value use and to enable and encourage spectrum to move to its highest value use, the Authority will make additional low-band and mid-band spectrum available for public mobile telecommunications services under this revised Plan.

1.2 Purpose

The purpose of the *Spectrum Plan for the Accommodation of Public Mobile Telecommunications Services* (the Plan) is to define the spectrum ranges, channel assignment plans, licensing conditions and technical operating conditions and specifications for the frequency bands that are available for public mobile telecommunications services.

1.3 Objectives

The Plan:

- 1. reviews and considers the global environment, including market and sector interests.
- 2. identifies the frequency ranges, assignment plans and spectrum caps that will be allocated for the provision of public mobile telecommunications services.
- 3. outlines the licensing process for the assignment of frequency ranges, including any specific licensing conditions.
- 4. defines the technical operating conditions and specifications to be imposed on the licensed radiocommunications systems in the allocated frequency ranges.

1.4 Scope

This Plan specifies the spectrum bands that have been allocated by the Authority for the provision of public cellular mobile telecommunications services, the allotment of channels within and how those bands will be licensed to the respective concessionaires. The bands contained in this Plan accommodate the deployment of second, third, fourth and fifth generation technologies for mobile services. The Plan does not address spectrum pricing for mobile services nor the allocation and licensing of spectrum bands for satellite broadband services, broadband wireless access, including fixed wireless access, services and private mobile networks.

The Plan is a subset of the *National Spectrum Plan* (NSP), which provides the overall framework for the regulation of spectrum, in an orderly, efficient manner, in accordance with the Authority's mandate under the Act.

1.5 Relevant Legislation

The following sections of the Act inform this Plan:

Section (18) (1) (i):

Subject to the provisions of this Act, the Authority may exercise such functions and powers as are imposed on it by this Act and in particular –

Plan, supervise, regulate and manage the use of the radio frequency spectrum, including –

- 1. the licensing and registration of radio frequencies and call signs to be used by all stations operating in Trinidad and Tobago or on any ship, aircraft, or other vessel or satellite registered in Trinidad and Tobago;
- 2. the allocation, assignment and reallocation or reassignment of frequency bands where necessary.

Section 21 (1):

No person shall operate a public telecommunications network, provide a public telecommunications service or broadcasting service, without a concession granted by the Minister.

Section 36 (1):

No person shall -

- 1. establish, operate or use a radio-communication service;
- 2. install, operate or use any radio transmitting equipment; or

3. establish, operate or use any radio-communication service on board any ship, aircraft, or other vessels in the territorial waters or territorial airspace of Trinidad and Tobago, other than a ship of war or a military aircraft or satellite registered in Trinidad and Tobago without a licence granted by the Authority.

Section 41 (1):

The Authority shall regulate the use of the spectrum in order to promote the economic and orderly utilisation of frequencies for the operation of all means of telecommunications and to recover the cost incurred in the management of the spectrum. Section 41 (2):

The Authority shall develop a spectrum plan in order to regulate the use of the spectrum.

Section 41 (3):

The National Spectrum Plan shall be made available to the public in the manner prescribed by the Authority.

Section 41 (4):

The National Spectrum Plan shall state how the spectrum shall be used and the procedures for licensing frequency bands.

1.6 Other Relevant Documents

Other relevant policies, plans and regulations, currently in effect, to be read along with this Plan include:

- 1. Authorisation Framework for the Telecommunications and Broadcasting Sectors of Trinidad and Tobago (TATT, 2005)
- 2. Spectrum Management Framework (TATT, 2022)
- 3. National Spectrum Plan (TATT, 2008)
- 4. *The Trinidad and Tobago Frequency Allocation Table* (8.3 kHz 3000 GHz) (TATT, 2019)
- 5. Spectrum Plan for the Accommodation of Broadband Wireless Access Services (TATT, 2008)
- 6. Consultative Document on the Framework for Fifth Generation (5G) Public Mobile Telecommunications Networks (second of Two Rounds) (TATT, 2023)

These documents can be found on the Authority's website, <u>www.tatt.org.tt</u>

1.7 Review Cycle

This Plan will normally be reviewed every four years to meet changing needs, taking into account technological advancements and regional allocations, but may be reviewed at any time at the discretion of the Authority based on proposals for immediate modification submitted by stakeholders or members of the public. The Authority will review the document and, if necessary, make modifications in consultation with stakeholders, to ensure the Plan is guided by appropriate policy guidelines and objectives.

Questions or concerns regarding the maintenance of the Plan may be directed to the Authority via e-mail at <u>consultation@tatt.org.tt</u>.

1.8 Consultation Process

In accordance with its *Procedures for Consultation in the Telecommunications and Broadcasting Sectors of Trinidad and Tobago* (TATT 2021), the Authority will seek the views of stakeholders and the public on this Plan. The Plan will undergo two rounds of public consultation. Each round shall be at least four weeks in duration. Comments from each round will be reviewed and incorporated where necessary, relevant and useful to the development of the local telecommunications sector.

1.9 Definitions

Equivalent isotropically radiated power (EIRP): the product of the power supplied to the antenna and the antenna gain in a given direction relative to an isotropic antenna (absolute or isotropic gain) (ITU-R 2020)

Effective radiated power (ERP) (in a given direction): the product of the power supplied to the antenna and its gain relative to a half-wave dipole in a given direction (ITU-R 2020))

Harmful interference: interference that endangers the functioning of telecommunications so as to impede, degrade, obstruct or interrupt a telecommunications service (the Act)

Primary service: a radiocommunications service for which stations can claim protection from harmful interference from stations of a secondary service (ITU-R 2020)

Public telecommunications network: a telecommunications network used to provide a public telecommunications service (the Act)

Public telecommunications service: a telecommunications service, including a public telephone service, offered to members of the general public, whereby one user can communicate with any other user in real time, regardless of the technology used to provide such service (the Act)

Secondary service: a radiocommunications service for which stations shall not cause harmful interference to stations of primary services and cannot claim protection from interference from stations of primary services (ITU-R 2020)

Station: one or more transmitters or receivers or a combination of transmitters and receivers, including the accessory equipment, necessary at one location for carrying on a radiocommunications service or radio astronomy service (ITU-R 2020)

2 Considerations for the Accommodation of Public Mobile Telecommunications Services

2.1 Global Environment

Cellular mobile technologies continue to evolve with new generations being released approximately every decade. Fifth generation (5G) technology is the latest cellular mobile platform available. Since the first commercial deployment of 5G in April 2019, globally, 200 cellular operators in more than 80 markets now offer 5G services (ITU 2022). Fourth generation (4G) cellular mobile technology is also still widely deployed. In markets where 4G networks are deployed, 4G technologies typically operate in parallel with earlier generation technologies, in many cases with both second generation (2G) and third generation (3G). IMT refers to the entire family of technology specifications for mobile broadband systems. IMT-2000 refers to the family of 3G, IMT-advanced refers to 4G and IMT-2020 refers to 5G technology specifications.

This technological revolution is accompanied by a corresponding evolution in spectrum use. Planning must, therefore, consider spectrum allocation for all generations of technologies in deployment. The International Telecommunications Union (ITU) has identified spectrum for IMT for the provision of public mobile telecommunications networks and services. Table 1 lists the various frequency bands identified for IMT. These bands are allocated to the mobile services in Article 5 of the ITU Radiocommunication (ITU-R) Radio Regulations, and footnotes are used to identify the bands for IMT. For example, footnote 5.384A identifies several bands for IMT. Footnote 5.384A states:

The frequency bands 1 710-1 885 MHz, 2 300-2 400 MHz and 2 500-2 690 MHz, or portions thereof, are identified for use by administrations wishing to implement International Mobile Telecommunications (IMT) in accordance with Resolution 223 (Rev.WRC-15). This identification does not preclude the use of these frequency bands by any application of the services to which they are allocated and does not establish priority in the Radio Regulations.

Band Category	Band (MHz)	Footnotes Identifying the Band for IMT (ITU-R Region 2 and Global Footnotes are bolded)
Low-band ¹	450-470	5.286AA
	470–698	5.295 , 5.296A, 5.308A
	698–960	5.313A, 5.317A
Mid-band ²	1427–1518	5.341A, 5.341B , 5.341C, 5.346, 5.346A
	1710-2025	5.384A, 5.388
	2110-2200	5.388
	2300-2400	5.384A
	2500-2690	5.384A
	3300-3400	5.429B, 5.429D , 5.429F
	3400-3600	5.430A, 5.431B , 5.432A, 5.432B, 5.433A
	3600-3700	5.434
	4800-4990	5.441A , 5.441B
High-band ³	24250-27500	5.532AB
	37000-43500	5.550B
	45500-47000	5.553A
	47200-48200	5.553B
	66000-71000	5.559AA

Table 1: Frequency bands identified for IMT

(Source: ITU-R Radio Regulations Resolutions and Recommendations Edition of 2020)

At the ITU, work has begun on developing the next IMT standard, IMT systems for 2030 and beyond, which will be known as sixth generation (6G). ITU-R Study Group 5 Working Party 5D (Terrestrial Services) is preparing a "vision" recommendation for the next generation of mobile technologies for 2030 and beyond (ITU 2022). This recommendation will be completed within the 2019-2023 study cycle (ITU 2022).

¹ Low bands are frequency bands below 1 GHz.

 $^{^{2}}$ Mid bands are frequency bands in the range 1–7 GHz.

³ High-bands or mmWave spectrum are the 26 GHz, 28 GHz, 40 GHz and 66–71 GHz frequency bands.

Figure 1 illustrates the low-band and mid-band frequency bands that are used for cellular mobile services globally.



Figure 1: Cellular mobile frequency bands (low-band and mid-band spectrum)

2.2 National Considerations

The adoption of 5G can be accelerated within the spectrum currently used for 4G. The expectation is that the 700 MHz, 850 MHz, 1900 MHz and 1.7/2.1 GHz bands could be used to accommodate both existing and 5G technology. The channel plans of these frequency bands were therefore optimised to accommodate both. Spectrum caps across multiple bands were also adopted to enable larger spectrum assignments within bands to facilitate 5G deployments, and simultaneously freeing spectrum in neighbouring bands with similar propagation characteristics. Additionally, mid-band spectrum in the 2.5 GHz and 3.5 GHz bands was included as these bands offer a unique mixture of coverage and capacity for mobile 5G services. Consideration was given to the existing services in these frequency bands.

High-band spectrum will not be considered for public mobile telecommunications services at this time. When global deployments increase, the end-user device and network equipment ecosystems mature and there is a local demand for high-band spectrum, the Plan may be revised to include high-band spectrum for the provision of public mobile telecommunications services.

To optimally allocate and adequately plan the use of the 700 MHz, 850 MHz, 1900 MHz, 1.7/ 2.1 GHz, 2.5 GHz and lower 3.5 GHz bands for the accommodation of public mobile telecommunications services, the Authority considered:

- 1. the frequency bands allocated to mobile service, in accordance with ITU-R Region 2 *Table of Frequency Allocations* and the *Trinidad and Tobago Frequency Allocation Table* (TTFAT).
- 2. the spectrum used for licensed public mobile telecommunications services in Trinidad and Tobago.
- 3. the availability of spectrum in Trinidad and Tobago to accommodate public mobile telecommunications services.
- 4. the appropriate licensing method for the assignment of spectrum to users.
- 5. the assignment and utilisation of spectrum to facilitate telecommunications infrastructure growth and the fulfilment of the national digital strategy.

These considerations are summarised in Table 2.

ITU-R Recommended Frequency Range of Operation	Trinidad and Tobago Frequency Allocation Table (TTFAT)	Current Spectrum Availability
700 MHz band: (698–806 MHz)	The frequency range 698– 806 MHz is allocated in TTFAT to mobile and broadcasting services as co-primary services, and to fixed services as the secondary service.	 The 700 MHz band is allocated to public mobile services, with two existing operators assigned spectrum in this band. 20 MHz is available in this band for the provision of public mobile telecommunications services. 10 MHz of spectrum is allotted for future use. 20 MHz of spectrum is allotted for the provision of public protection and disaster relief (PPDR) services.
850 MHz band: (824–849/869–894 MHz)	The frequency ranges 824– 849/869–894 MHz span two frequency allocations in TTFAT: 806–890 MHz and 890–902 MHz Mobile service is the primary service in both ranges.	 The 850 MHz band is allocated to public mobile telecommunications services, with the two existing operators assigned spectrum in this band. 12 MHz is available in this band for the provision of public mobile telecommunications services. 10 MHz is allotted for future use.

	Table 2	: Freq	uency	allocations	for	cellular	mobile	networks
--	---------	--------	-------	-------------	-----	----------	--------	----------

ITU-R Recommended Frequency Range of Operation	Trinidad and Tobago Frequency Allocation Table (TTFAT)	Current Spectrum Availability
1900 MHz band: (1850–1920/1930– 2000 MHz)	The frequency ranges 1850–1920/1930–2000 MHz span four frequency allocations in TTFAT: 1710–1930 MHz, 1930– 1970 MHz, 1970–1980 MHz and 1980–2010 MHz. Mobile service is the primary service in all the ranges.	The 1900 MHz band (1850–1910 MHz/1930–1990 MHz) is allocated to public mobile services, with the two existing operators assigned spectrum in this band. 40 MHz is available in this band for the provision of public mobile telecommunications services. Considering that the extended 1900 MHz band is now being utilised for the deployment of cellular services in ITU-R Region 2 countries, an additional 10 MHz (1910–1915 MHz and 1990–1995 MHz) is available in the 1900 MHz band for the provision of public mobile telecommunications services, subject to a spectrum audit to verify available spectrum.
1.7/2.1 GHz band: (1710–1780/2110– 2180 MHz)	The frequency ranges 1710 -1755 MHz and 2110- 2155 MHz span five frequency allocations in TTFAT: 1710-1930 MHz, 2110- 2120 MHz, 2120-2160 MHz, 2160-2170 MHz and 2170-2200 MHz. Mobile service is the primary service in all the ranges.	The 1.7/2.1 GHz band (1710–1755 MHz/2110–2155 MHz) is allocated to public mobile services, with the two existing operators assigned spectrum in this band. 60 MHz is available in this band for the provision of public mobile telecommunications services. Considering that the extended 1.7/2.1 GHz band is now being utilised for the deployment of cellular services in ITU-R Region 2 countries, an additional 50 MHz (1755–1780 MHz and 2155–2180 MHz) is available in the 1.7/2.1 GHz band for the provision of public mobile telecommunications services, subject to a spectrum audit to verify available spectrum.

ITU-R Recommended	Trinidad and Tobago	Current Spectrum Availability
Frequency Range of Operation	Frequency Allocation Table (TTFAT)	
2.5 GHz band: (2500– 2690 MHz)	The frequency range 2500– 2690 MHz spans four frequency allocations in TTFAT: 2500–2520 MHz, 2520– 2655 MHz, 2655–2670 MHz and 2670–2690 MHz. Mobile service is the primary service in all the ranges.	The 2.5 GHz band is allocated to broadband wireless access (BWA) services, with the two existing operators assigned spectrum based on a TDD channel plan. There is 90 MHz of unassigned spectrum (contiguous) in this band.
Lower 3.5 GHz band: (3.3–3.8 GHz)	The frequency range 3.3– 3.8 GHz spans four frequency allocations in TTFAT: 3300–3400 MHz, 3400– 3500 MHz, 3500–3600 MHz and 3600–3700 MHz. Mobile service is the primary service in all the ranges except 3300–3400 MHz.	The 3.3–3.4 GHz range is currently unassigned. The 3.4–3.7 GHz range is currently allocated to broadband wireless access services. Two existing licensees are assigned spectrum in the frequency range 3.4–3.6 GHz, based on a TDD channel plan. There is 140 MHz of unassigned spectrum (non-contiguous) in this band.

The Authority will be conducting monitoring exercises to verify that the additional spectrum in both the 1900 MHz and 1.7/2.1 GHz bands, and the spectrum in the 2.5 GHz and lower 3.5 GHz bands, are free from harmful interference. Furthermore, the Authority is aware of the possibility of harmful interference with neighbouring countries. The *ITU-R Radio Regulations* articulates the procedures by which countries can conduct frequency notification, coordination and treatment of harmful interference across borders. The Authority will be guided by these procedures should the need arise. As part of the implementation process, the Authority will issue the necessary notification to ITU-R upon assignment, which will enable and facilitate coordination processes with neighbouring countries when necessary.

In its continuing effort to make additional spectrum available for public mobile telecommunications services, and recognising the value of feedback from the industry, the Authority will consult with relevant stakeholders to assess any future candidate bands for public mobile telecommunications services. It is also the Authority's intention that other candidate IMT bands be considered for the provision of public mobile telecommunications services as demand and/or changes in the sector emerge.

3 Frequency Assignment Principles

The following principles undergird the frequency assignment plans for the accommodation of public mobile telecommunications services in Trinidad and Tobago:

- 1. The adopted frequency assignment plan for a specified band shall follow the relevant ITU-R recommendation, if applicable, and take into consideration the predominant frequency assignment plan utilised by mobile services in the particular frequency band.
- 2. All frequency assignment plans shall have a reference channel bandwidth that serves as the minimum assignable channel bandwidth. Frequency channels that require larger bandwidths can be achieved by concatenating multiple non-contiguous frequency channels of the reference channel bandwidth, which would equate to contiguous spectrum. All assignments to an operator shall be contiguous as far as possible.
- 3. Both frequency division duplexing (FDD) and time division duplexing (TDD) modes of operation will be supported and the frequency assignment plan shall specify the mode of operation.
- 4. Frequency assignments shall be made in accordance with the selected licensing process, as established by the Authority.
- 5. The frequency spectrum blocks or channels in a frequency assignment plan incorporate any necessary guard bands. Any necessary guard bands for entities authorised to use adjacent blocks or channels will be determined at such time that the licensees and the respective technologies to be deployed have been determined.
- 6. Spectrum caps shall be instituted in each band and across bands to limit the quantum of spectrum assigned to an individual user. The spectrum cap is the maximum quantum of spectrum that can be assigned to a licensee in a specified frequency band or in aggregate across bands. The spectrum caps shall ensure sufficient spectrum is available for assignment to up to three cellular mobile operators.
- 7. A licensee shall utilise the spectrum assigned in a manner that does not cause harmful interference to any other licensee. The licensee shall also employ in-band guard bands to mitigate harmful interference.
- 8. The maximum radio frequency (RF) output power limits may vary between different frequency bands, as propagation characteristics of the bands differ.

4 Frequency Assignment Plans for Public Mobile Telecommunications Services

The various frequency bands allocated for public mobile telecommunications services can be further subdivided into frequency channel allotments, predicated on the type(s) of technologies that can be employed, which will inform frequency assignment plans. These frequency assignment plans aim to maximise the efficient use of the allocated spectrum.

The following sub-sections outline the various frequency ranges under consideration. Each subsection further outlines the frequency assignment plan, the recommended licensing process and conditions, and the technical operating conditions and specifications for the radiocommunications systems operating in the stated frequency band.

The actual availability of frequency channels for public mobile telecommunications services will be determined following a spectrum audit to verify the availability of the spectrum prior to the implementation of the respective licensing process for each frequency band.

4.1 The 700 MHz Band (703–748/758–803 MHz)

4.1.1 Selection of Frequency Assignment Plan

The propagation characteristics of the spectrum in the 700 MHz band and the allowable power limits make it conducive to serving consumers over a large area. Both 4G and 5G cellular mobile technologies are deployed in the 700 MHz band.

There are two competing frequency assignment (channel) plans for the 700 MHz band. Figure 2 identifies the plans employed by the APT and the United States in the 700 MHz band.

APT/CITEL Band Plan 2x45 MHz		GP	
5 A5MHz	45MHz	3 MHz	
698MHz		806MHz	Mobile Station Transmit
US Band Plan 2x22 MHz			Base Station Transmit
GB 12MHz 12MHz 10MHz 6 MHz	Public Safety	'ublic afety	GB Guard Band
698MHz		806MHz	

Figure 2: 700 MHz band plans

The Authority adopted the APT 700 MHz band plan for the 700 MHz band, i.e., 3GPP Band 28 (3GPP 2014), for the provision of public domestic mobile telecommunications networks and services, due to regional and global adoption of this band plan, which has driven significant growth in the device and network equipment ecosystems.

The ITU-R, at the World Radiocommunication Conference 2015 (WRC-15) (ITU-R 2016), modified Resolution 646: Public Protection and Disaster Relief (first approved in 2007 at WRC-07) and resolved to encourage administrations to:

- 1. use harmonised frequency ranges for PPDR to the maximum extent possible, taking into account the national and regional requirements, and also allowing for consultation and cooperation with other concerned countries.
- 2. consider parts of the frequency range 694–894 MHz, as described in the most recent version of ITU-R Recommendation M.2015, when undertaking their national planning for PPDR applications, and broadband in particular, to achieve harmonisation.

It is within this context that consideration was given to the allocation of spectrum for PPDR within the frequency range 694–894 MHz, which is a designated range for IMT. Further to this, careful planning of the 700 MHz band (i.e., 698–806 MHz) is needed in ITU-R Region 2 countries (the Americas and the Caribbean), given the available mobile broadband technologies and the quantum of spectrum for allocation.

The US 700 MHz band plan is the only 700 MHz band plan that has a designated spectrum allocation for PPDR, i.e., the frequency ranges 788–798 MHz paired with 758–768 MHz, also known as 3GPP Band 14. This band plan has been adopted by Canada, Bolivia, Nicaragua, the United States and some English-speaking Caribbean countries. However, the APT 700 MHz band plan does not have a designated spectrum allocation for PPDR. Hence, Region 2 countries that

have adopted this plan, and wish to comply with the ITU resolution, require PPDR designations in the planning of the 700 MHz band.

For national security reasons, the Authority will maintain an exclusive allotment of 700 MHz spectrum for PPDR. Consistent with the quantum of spectrum allotted in the US 700 MHz band plan and the allotment by other jurisdictions for broadband PPDR, the Authority shall identify an allotment of 2×10 MHz in the 700 MHz band for PPDR.

4.1.2 Frequency Assignment Plan

The channel assignment plan outlined in Table 3 shall be adopted for the 700 MHz band and shall only accommodate the FDD mode of operation.

Blocks A and B (i.e., 2×10 MHz) shall be allotted for the provision of PPDR. This allows blocks C – I (i.e., 2×5 MHz each) for assignment to up to three cellular mobile operators.

This frequency assignment plan does not require the establishment of guard bands, as guard bands are established within the allotted spectrum blocks.

Band	Frequency Range/MHz		Block Name
	Mobile Station Transmit	Base Station Transmit	
	703–708	758–763	А
	708–713	763–768	В
	713–718	768–773	C
700 MH7	718–723	773–778	D
/00 101112	723–728	778–783	E
	728–733	783–788	F
	733–738	788–793	G
	738–743	793–798	Н
	743–748	798–803	Ι

Table 3: Frequency assignment plan for 700 MHz band

4.1.3 Licensing Process and Conditions

The rules for licensing are as follows:

- 1. A concession for the provision of a public domestic mobile telecommunications network and public telecommunications services is a prerequisite for the assignment of spectrum in the 700 MHz band.
- 2. The licensing of spectrum in the 700 MHz band shall be for the provision of public mobile telecommunications services on a national basis, save and except for an allotment to PPDR.
- 3. A cellular mobile spectrum licence shall be granted by the Authority, in order for spectrum in the 700 MHz band to be assigned. The minimum assignment shall be 10 MHz, (i.e., 2 x 5 MHz).
- 4. The allocated spectrum in the 700 MHz band shall be licensed in accordance with the frequency assignment plan (see Table 3).
- 5. The spectrum cap for the 700 MHz band shall be 40 MHz (i.e., 2 x 20 MHz).
- 6. Each licensee assigned spectrum blocks in the 700 MHz and 850 MHz bands shall not exceed a total spectrum cap of 50 MHz (i.e., 2 x 25 MHz). This allows for up to three cellular mobile operators to be assigned spectrum in these bands.
- 7. The assignment of spectrum, either to new spectrum licensees or where there is preference for specified spectrum blocks, shall be via a competitive licensing process, as determined by the Authority.
- 8. The assignment of spectrum to existing and eligible concessionaires, where there is no preference for specified spectrum blocks, shall be via an assignment process determined by the Authority.
- 9. The Authority shall reserve an allocation of at least 2 x 10 MHz of contiguous spectrum in either the 700 MHz or 850 MHz band for future demand.

4.1.4 Technical Operating Conditions and Specifications

To operate public mobile telecommunications services in the 700 MHz band, licensees shall not exceed the maximum technical operating conditions and specifications identified in Table 4.

Parameter	Constraint/Maximum Value	Comments
Base station maximum effective radiated power (ERP)	1000 W	The ERP shall not exceed 1000 W per emission.
Mobile station maximum ERP	3 W	Mobile stations shall employ a means to limit power to the minimum level? necessary for successful communication.
Modulation scheme	Digital	Any digital modulation technique, e.g., BPSK and QPSK
Out-of-band emission limits	-43 dBW	Attenuation (α) on max power (P) of emissions calculated using: $\alpha = 43+10\log(P)$ (For base stations P=1000 W and for mobile stations P=3 W)
Standardisation	N/A	FCC, Industry Canada, ETSI

Table 4: Maximum technical operating specifications for the 700 MHz band⁴

Notwithstanding the parameters identified in Table 4, amended or additional technical operating conditions may be instituted in accordance with the Act. These revisions shall be identified in the respective schedule of the licence document for the specific radiocommunications technology deployed.

⁴ These specifications were developed in accordance with the *Code of Federal Regulations*, Title 47, Part 27 (i.e., FCC Rules).

4.2 The 850 MHz Band (824–849/869–894 MHz)

4.2.1 Selection of Frequency Assignment Plan

Historically, two predominant band plans existed globally for 2G IMT technology – those of North America and of the European Union. Administrations worldwide developed band plans that either adhere completely to one of these plans or use a blend of both designations. North America has operated mobile telecommunications systems in the 800 MHz (824–849/869–894 MHz) and 1900 MHz (1850–1910/1930–1990 MHz) frequency bands, whereas counterpart systems in Europe operated in the 900 MHz (880–915/925–960 MHz) and 1800 MHz (1710–1785/1805–1880 MHz) bands.

Trinidad and Tobago adopted the North American band plans for the 850 MHz bands. The 850 MHz band supports the implementation of various technologies, including 2G in the GSM-850 band and UMTS, LTE and 5G in the 3GPP band 5/n5.

4.2.2 Frequency Assignment Plan

The Authority's channel assignment plan for the 850 MHz band shall be based on the North American band plan, allowing for various technologies, for the provision of public mobile telecommunications services, as shown in Table 5. This channel assignment plan shall only accommodate the FDD mode of operation.

Blocks A to E shall be available for assignment for up to three cellular mobile operators. This frequency assignment plan does not require the establishment of guard bands, as guard bands are established, if required, within the allotted spectrum blocks.

Band	Frequency Range/MHz		Plack Name
	Mobile Station Transmit	Base Station Transmit	DIOCK INAILIE
	824-829	869-874	А
850 MHz	829-831.5	874-876.5	Β'
	831.5-834	876.5-879	B"
	834–839	879–884	С
	839-841.5	884-886.5	D'
	841.5-844	886.5-889	D"
	844–849	889-894	E

Table 5: Frequency assignment plan for 850 MHz band

4.2.3 Licensing Process and Conditions

The rules for licensing are as follows:

- 1. A concession for the provision of a public domestic mobile telecommunications network and public telecommunications services is a prerequisite for the assignment of spectrum in the 850 MHz band.
- 2. The licensing of spectrum in the 850 MHz band shall be for the provision of public mobile telecommunications services, on a national basis.
- 3. A cellular mobile spectrum licence shall be granted in order for spectrum in the 850 MHz band to be assigned.
- 4. The allocated spectrum in the 850 MHz band shall be licensed in accordance with the frequency assignment plan shown in Table 5. The minimum assignment shall be 10 MHz, i.e., 2 x 5 MHz.
- 5. The spectrum cap for the 850 MHz band shall be 30 MHz, (i.e., 2 x 15 MHz).
- 6. Each licensee assigned spectrum blocks in the 700 MHz and 850 MHz bands shall not exceed a total spectrum cap of 50 MHz (i.e., 2 x 25 MHz). This allows for up to three cellular mobile operators to be assigned spectrum in these bands.
- 7. The assignment of spectrum, to new spectrum licensees or where there is preference for specified spectrum blocks, shall be via a competitive licensing process, as determined by the Authority.
- 8. The assignment of spectrum to existing and eligible concessionaires, where there is no preference for specified spectrum blocks, shall be via an assignment process prescribed by the Authority.
- 9. The Authority shall reserve an allocation of at least 2 x 10 MHz of contiguous spectrum in either the 700 MHz or 850 MHz band for future demand.

4.2.4 Technical Operating Conditions and Specifications

To operate public mobile telecommunications services in the 850 MHz band, licensees shall not exceed the maximum technical operating conditions and specifications identified in Table 6.

Parameter	Constraint/Maximum Value	Comments	
Base station maximum ERP	500 W	The ERP shall not exceed 500 W per emission.	
Mobile station maximum ERP	7 W	Mobile stations shall employ a means to limit power to the minimum necessary for successful communication.	
Modulation scheme	Digital	Any digital modulation technique e.g. BPSK and QPSK	
Out-of-band emission limits	-43 dBW	Attenuation (α) on max power (P) o emissions calculated using: $\alpha = 43+10\log(P)$ (For base stations P=500 W, and for mobile stations P=7 W)	
Standardisation	N/A	FCC, Industry Canada, ETSI	

Table 6: Maximum technical operating specifications for the 850 MHz band⁵

Notwithstanding the parameters identified in Table 6, amended or additional technical operating conditions may be instituted in accordance with the Act. Such revisions shall be identified in the respective schedule of the licence document for the specific radiocommunications technology deployed.

⁵ These specifications were developed in accordance with the *Code of Federal Regulations*, Title 47, Part 22 (i.e., FCC Rules).

4.3 The 1900 MHz Band (1850–1915/1930–1995 MHz)

4.3.1 Selection of a Frequency Assignment Plan

The 1900 MHz band, called the personal communications services (PCS) block in North America, is used throughout the region for the provision of mobile voice and data services. The North American allocation comprises two sub-bands – the lower sub-band and the upper sub-band. The sub-bands are divided into seven paired blocks, three 15 MHz blocks and four 5 MHz blocks.

The 1900 MHz band supports the implementation of various technologies, including UMTS (3GPP band 2, 1850–1910/1930–1990 MHz and 3GPP band 25, 1850–1915/1930–1995 MHz); LTE (3GPP band 2 and band 25); and 5G (3GPP band n2 and n25).

4.3.2 Frequency Assignment Plan

The Authority's assignment plan for the 1900 MHz band will be based on the North American PCS band plan, for the provision of public mobile telecommunications services, as shown in Table 7. This channel assignment plan shall only accommodate the FDD mode of operation.

This frequency assignment plan does not require the establishment of guard bands, as guard bands are established, if required, within the allotted spectrum blocks.

Band	Frequency Range/MHz		
	Mobile Station Transmit	Base Station Transmit	Block Name
	1850–1865	1930–1945	А
	1865–1870	1945–1950	D
	1870–1875	1950–1955	B1
1900 MHz	1875–1880	1955–1960	B2
	1880–1885	1960–1965	B3
	1885–1890	1965–1970	Е
	1890–1895	1970–1975	F
	1895–1910	1975–1990	С
	1910–1915	1990–1995	G

Table 7: Frequency	assignment plan	for 1900 MHz band
--------------------	-----------------	-------------------

4.3.3 Licensing Process and Conditions

The rules for licensing are as follows:

- 1. A concession for the provision of a public domestic mobile telecommunications network and public telecommunications services is a prerequisite for the assignment of spectrum in the 1900 MHz band.
- 2. The licensing of spectrum in the 1900 MHz band shall be for the provision of public mobile telecommunications services, on a national basis.
- 3. A cellular mobile spectrum licence shall be granted in order for spectrum in the 1900 MHz band to be assigned.
- 4. The allocated spectrum in the 1900 MHz band shall be licensed in accordance with the frequency assignment plan shown in Table 7. The minimum assignment shall be 10 MHz (i.e., 2 x 5 MHz).
- 5. The spectrum cap for the 1900 MHz band shall be 70 MHz (i.e., 2 x 35 MHz).
- 6. Each licensee assigned spectrum blocks in the 1900 MHz and 1.7/2.1 GHz bands shall not exceed a total spectrum cap of 90 MHz (i.e., 2 x 45 MHz). This allows for up to three cellular mobile operators to be assigned spectrum in these bands.
- 7. The assignment of spectrum, to new spectrum licensees or where there is a preference for specified spectrum blocks, shall be via a competitive licensing process, as determined by the Authority.
- 8. The assignment of spectrum to existing and eligible concessionaires, where there is no preference for specified spectrum blocks, shall be via an assignment process determined by the Authority.

4.3.4 Technical Operating Conditions and Specifications

To operate public mobile telecommunications services in the 1900 MHz band, licensees shall not exceed the maximum technical operating conditions and specifications identified in Table 8.

Parameter	Constraint/Maximum Value	Comments
Base station maximum equivalent isotropically radiated power (EIRP)	1640 W/MHz	No more than 1640 W EIRP in any 1 MHz band segment
Mobile station maximum EIRP	2 W	Mobile stations shall employ a means to limit power to the minimum necessary for successful communication.
Modulation scheme	Digital	Any digital modulation technique e.g., BPSK and QPSK
Out-of-band emission limits	-43 dBW	Attenuation (α) on max power (P) of emissions calculated using: $\alpha =$ 43+10log (P) (For base stations P=1640 W and for mobile stations P=2 W)
Standardisation	N/A	FCC, Industry Canada, ETSI

Table 8: Maximum technical operating specifications for the 1900 MHz band⁶

Notwithstanding the parameters identified in Table 8, amended or additional technical operating conditions may be instituted in accordance with the Act. Revisions shall be identified in the respective schedule of the licence document for the specific radiocommunications technology deployed.

⁶ These specifications were developed in accordance with the *Code of Federal Regulations*, Title 47, Part 24 (i.e., FCC Rules).

4.4 The 1.7/2.1 GHz Band (1710–1780/2110–2180 MHz)

4.4.1 Selection of Frequency Assignment Plan

The 1.7/2.1 GHz band supports the implementation of different technologies, including UMTS (3GPP band 4, 1710–1755 MHz/2110–2155 MHz); LTE (3GPP band 4 and band 66, 1710–1780/2110–2200); and 5G (3GPP band n66, 1710–1780/2110–2200).

The Report and Order FCC 03-251 established rules to license the AWS band in North America in the 1710–1755 and 2110–2155 MHz frequency range (FCC 2003). Similarly, Report and Order FCC 14-31 established rules for the use of 1755–1780 and 2155–2180 (FCC 2014). Both bands 4 and 66 are used throughout ITU-R Region 2 countries for the provision of cellular mobile services. It should be noted that only up to 2180 MHz in band 66 is used for cellular mobile services, as 2180–2200 MHz is being considered for mobile-satellite service.

Trinidad and Tobago considers the extended AWS band (i.e. 1710–1780/2110–2180 MHz) based on 3GPP band 66/n66 suitable for allocation to public mobile telecommunications services, due to its adoption across ITU-R Region 2 and its large mobile handset ecosystem across multiple generations of cellular mobile technologies, including those that operate in the subset band 1710–1755/2110–2155 MHz band based on 3GPP band 4.

4.4.2 Frequency Assignment Plan

Fourteen paired 5 MHz spectrum blocks will be available for assignment. The frequency assignment plan for the AWS band plan is shown in Table 9, and it takes into consideration the assignment of spectrum to up to three cellular mobile operators.

This frequency assignment plan does not require the establishment of guard bands, as guard bands are established, if required, within the allotted spectrum blocks, and shall only accommodate the FDD mode of operation.

Band	Frequency Range/ MHz		Dia de Marra
	Mobile Station Transmit	Base Station Transmit	Block Name
	1710–1715	2110-2115	А
	1715–1720	2115-2120	В
	1720–1725	2120-2125	С
	1725–1730	2125–2130	D
	1730–1735	2130–2135	Е
1 7/2 1 011	1735–1740	2135-2140	F
1.7/2.1 GHz	1740–1745	2140-2145	G
	1745–1750	2145–2150	Н
	1750–1755	2150-2155	Ι
	1755–1760	2155-2160	J
	1760–1765	2160-2165	K
	1765–1770	2165-2170	L
	1770–1775	2170–2175	М
	1775–1780	2175-2180	N

Table 9: Frequency assignment plan for the AWS band

4.4.3 Licensing Process and Conditions

The rules for licensing are as follows:

- 1. A concession for the provision of a public domestic mobile telecommunications network and public telecommunications services is a prerequisite for the assignment of spectrum in the 1.7/2.1 GHz band.
- 2. The licensing of spectrum in the 1.7/2.1 GHz band shall be for the provision of public mobile telecommunications services, on a national basis.
- 3. A cellular mobile spectrum licence shall be granted in order for spectrum in the 1.7/2.1 GHz band to be assigned.
- 4. The allocated spectrum in the 1.7/2.1 GHz band shall be licensed in accordance with the frequency assignment plan shown in Table 9.
- 5. The spectrum cap for the 1.7/2.1 GHz band will be 70 MHz (i.e., 2 x 35 MHz) per cellular mobile operator.

- 6. Each licensee assigned spectrum blocks in the 1900 MHz and 1.7/2.1 GHz bands shall not exceed a total spectrum cap of 90 MHz (i.e., 2 x 45 MHz). This allows for up to three cellular mobile operators to be assigned spectrum in these bands.
- 7. The assignment of spectrum, to new spectrum licensees or where there is preference for specified spectrum blocks, shall be via a competitive licensing process, as determined by the Authority.
- 8. The assignment of spectrum to existing and eligible concessionaires, where there is no preference for specified spectrum blocks, shall be via an assignment process determined by the Authority.

4.4.4 Technical Operating Conditions and Specifications

To operate public mobile telecommunications services in the AWS band, licensees shall not exceed the maximum technical operating conditions and specifications identified in Table 10.

Parameter	Constraint/Maximum Value	Comments	
Base station maximum EIRP	1640 W	No more than 1640 W EIRP in any 1 MHz band segment	
Mobile station maximum EIRP	1 W	Mobile stations shall employ a means to limit power to the minimum necessary for successful communications.	
Modulation scheme	Digital	Any digital modulation technique, e.g., BPSK and QPSK	

Table 10: Maximum technical operating specifications for the AWS band⁷

⁷ These specifications were developed in accordance with the *Code of Federal Regulations*, Title 47, Part 22 (i.e., FCC Rules).

Parameter	Constraint/Maximum Value	Comments
Out-of-band emissio limits	¹ -43 dB	The power of any emission outside the licensee's frequency block shall be attenuated below the transmitter power (P) by at least 43+10log (P). Attenuation (α) on max power (P) of emissions calculated using: $\alpha = 43+10log$ (P) (For base stations P=1640 W and for mobile stations P=1 W)
Standardisation	N/A	FCC, Industry Canada

Notwithstanding the parameters identified in Table 10, amended or additional technical operating conditions may be instituted in accordance with the Act. Such revisions shall be identified in the respective schedule of the licence document for the specific radiocommunications technology deployed.

4.5 The 2.5 GHz Band (2496–2690 MHz)

4.5.1 Selection of Frequency Assignment Plan

The 2.5 GHz band supports 3G, 4G and 5G cellular mobile technologies. There are two predominant frequency assignment plans for the 2.5 GHz band. Figure 3 presents the frequency arrangements that support FDD and TDD in the 2.5 GHz band.



Figure 3: 2.5 GHz band plans

The FDD band plan contains a 50 MHz duplex spacing that can be used as a supplemental downlink band, aggregated with downlink spectrum from other bands. The duplex spacing could also be used for TDD operations, to deploy mixed FDD/TDD channels in the band.

The 2.5 GHz band is currently allocated to BWA service. There are assignments to two operators in the band, totalling 100 MHz. The BWA assignments are based on a TDD band plan. 90 MHz of contiguous spectrum is unassigned and available for assignment to cellular mobile operators in the frequency range 2600–2690 MHz.

Considering the spectrum that is available for assignment to cellular mobile operators, the FDD band plan was not considered for the 2.5 GHz band.

The TDD band plan for the 2.5 GHz band is based on 3GPP bands 41/n41 and supports the deployment of 4G and 5G IMT technologies. There is a mature 4G handset ecosystem that supports 3GPP band 41 and a growing 5G handset ecosystem that supports 3GPP band n41. With this channel assignment plan, the 90 MHz contiguous and unassigned spectrum will be available for public mobile telecommunications services. Importantly, the *Spectrum Plan for the Accommodation of Broadband Wireless Access Services* will be revised and the spectrum allocation in the 2.5 GHz band for BWA services will be amended.

4.5.2 Frequency Assignment Plan

The Authority's assignment plan for the 2.5 GHz band will be based on the 3GPP TDD band 41/n41, for the provision of public mobile telecommunications services, as shown in Table 11.

This frequency assignment plan does not require the establishment of guard bands, as guard bands are established, if required, within the allotted spectrum blocks.

Band	Frequency Range/MHz	Block Name
	Mobile/Base Station Transmit	
2.5 GHz	2600–2645	А
	2645-2690	В

Fable 11: Frequer	ncy assignment	plan for 2.5 GHz band
-------------------	----------------	-----------------------

4.5.3 Licensing Process and Conditions

The rules for licensing are as follows:

- 1. A concession for the provision of a public domestic mobile telecommunications network and public telecommunications services is a prerequisite for the assignment of spectrum in the 2.5 GHz band.
- 2. The licensing of spectrum in the 2.5 GHz band shall be for the provision of public mobile telecommunications services, on a national basis.
- 3. A cellular mobile spectrum licence shall be granted in order for spectrum in the 2.5 GHz band to be assigned.
- 4. The allocated spectrum in the 2.5 GHz band shall be licensed in accordance with the frequency assignment plan shown in Table 11. The minimum assignment shall be 45 MHz.
- 5. The spectrum cap for the 2.5 GHz band shall be 90 MHz.
- 6. Each licensee assigned spectrum blocks in the 2.5 GHz and lower 3.5 GHz bands shall not exceed a total spectrum cap of 100 MHz. This allows for up to three cellular mobile operators to be assigned spectrum in these bands.
- 7. The assignment of spectrum shall be via a competitive licensing process which shall include an auction, as determined by the Authority. Any fee determined from this process will be applied to any other spectrum in the entire 2.5 GHz band used for public mobile telecommunications services by an operator with a concession for the provision of a public domestic mobile telecommunications network and public telecommunications services.

4.5.4 Technical Operating Conditions and Specifications

To operate public mobile telecommunications services in the 2.5 GHz band, licensees shall not exceed the maximum technical operating conditions and specifications identified in Table 12.

Parameter	Constraint/Maximum Value	Comments
Base station maximum EIRP	1640 W/MHz	No more than 1640 W EIRP in any 1 MHz band segment
Mobile station maximum EIRP	2 W	Mobile stations shall employ a means to limit power to the minimum necessary for successful communication.
Modulation scheme	Digital	Any digital modulation technique e.g., BPSK and QPSK
Out-of-band emission limits	Base stations: -43 dBW Mobile stations: -40 dBW	 Attenuation (α) on max power (P) of emissions calculated using: α = 43+10log (P) for base stations For mobile stations, using: 1. α = 40+10log (P) from the channel edge to 5 MHz away 2. α = 43+10log (P) between 5 MHz and X MHz from the channel edge. 3. α = 55+10log (P) at X MHz and beyond from the channel edge. (X is the equipment occupied bandwidth) (Limit for base stations P=1640 W and for mobile stations P=2 W)
Standardisation	N/A	FCC, Industry Canada

Table 12: Maximum technical operating specifications for the 2.5 GHz band⁸

⁸ These specifications were developed in accordance with Standard Radio System Plan SRSP-517 and Radio Standards Specification RSS-199.

Notwithstanding the parameters identified in Table 12, amended or additional technical operating conditions may be instituted in accordance with the Act. Revisions shall be identified in the respective schedule of the licence document for the specific radiocommunications technology deployed.

4.6 The Lower 3.5 GHz Band (3300–3800 MHz)

4.6.1 Selection of Frequency Assignment Plan

The 3.5 GHz band (3.3–4.2 GHz) consists of mid-band spectrum that complements the sub-1 GHz and other lower bands to provide both capacity and coverage. The 3.5 GHz band is made up of the satellite C-band that is now primarily used for cellular mobile services and fixed wireless access (FWA) services. The lower 3.5 GHz band is considered prime spectrum for the deployment of IMT-2020 technology, due to the large quantum of spectrum in the band.

In keeping with the *Framework for Fifth Generation (5G) Public Mobile Telecommunications Networks* the upper 3.5 GHz band (3.7–4.2 GHz) would not be considered for allocation to public mobile telecommunications services because of the current state of licensees in the band in Trinidad and Tobago, and international references on 5G and radio altimeters coexistence. Only the lower 3.5 GHz band (3.3–3.7 GHz) will be considered for the allocation to public mobile telecommunications services.

Within the lower 3.5 GHz band, BWA network operators are assigned spectrum in the range 3.4–3.6 GHz, totalling 100 MHz. There are also assignments in 3.6–3.7 GHz for other services. Two blocks totalling 190 MHz of contiguous spectrum in the ranges 3.3–3.4 GHz and from 3.55–3.64 GHz are available.

The Spectrum Plan for the Accommodation of Broadband Wireless Access Services will be revised and the spectrum allocation in the 3.5 GHz band for BWA services will be amended.

Only a frequency assignment plan that supports a TDD mode of operation can be considered for the lower 3.5 GHz band. 3GPP band n78 (3.3–3.8 GHz), a subset of n77 (3.3–4.2 GHz), spans the lower 3.5 GHz band. The band only supports 5G technology and has a growing handset ecosystem.

4.6.2 Frequency Assignment Plan

The Authority's frequency assignment plan for the lower 3.5 GHz band is shown in Table 13 and is a subset of the 3GPP TDD band n78.

This frequency assignment plan does not require the establishment of guard bands, as guard bands are established, if required, within the allotted spectrum blocks.

Band	Frequency Range/MHz	Block Name
	Mobile/Base Station Transmit	
	3300–3350	А
3.5 GHz	3350–3400	В
	3550–3595	С
	3595–3640	D

Table 13: Frequency assignment plan for the lower 3.5 GHz band

4.6.3 Licensing Process and Conditions

The rules for licensing are as follows:

- 1. A concession for the provision of a public domestic mobile telecommunications network and public telecommunications services is a prerequisite for the assignment of spectrum in the Lower 3.5 GHz band.
- 2. The licensing of spectrum in the lower 3.5 GHz band shall be for the provision of public mobile telecommunications services, on a national basis.
- 3. A cellular mobile spectrum licence shall be granted in order to assign spectrum in the lower 3.5 GHz band.
- 4. The allocated spectrum in the lower 3.5 GHz band shall be licensed in accordance with the frequency assignment plan shown in Table 13. The minimum assignment shall be 45 MHz.
- 5. The spectrum cap for the lower 3.5 GHz band shall be 100 MHz.
- 6. Each licensee assigned spectrum blocks in the 2.5 GHz and lower 3.5 GHz bands shall not exceed a total spectrum cap of 100 MHz. This allows for up to three cellular mobile operators to be assigned spectrum in these bands.
- 7. The assignment of spectrum shall be via a competitive licensing process which shall include an auction, as determined by the Authority.

4.6.4 Technical Operating Conditions and Specifications

To operate public mobile telecommunications services in the lower 3.5 GHz band, licensees shall not exceed the maximum technical operating conditions and specifications identified in Table 14.

Parameter	Constraint/Maximum Value	Comments
Base station maximum EIRP	1640 W/MHz	No more than 1640 W EIRP in any 1 MHz band segment
Mobile station maximum EIRP	1 W	Mobile stations shall employ a means to limit power to the minimum necessary for successful communication.
Modulation scheme	Digital	Any digital modulation technique e.g., BPSK and QPSK
Out-of-band emission limits	-43 dBW	
Standardisation	N/A	FCC, Industry Canada

Table 14: Maximum technical operating specifications for the lower 3.5 GHz band⁹

Notwithstanding the parameters identified in Table 14, amended or additional technical operating conditions may be instituted in accordance with the Act. Revisions shall be identified in the respective schedule of the licence document for the specific radiocommunications technology deployed.

⁹ These specifications were developed in accordance with the *Code of Federal Regulations*, Title 47, Part 27 (i.e., FCC Rules).

References

- 3GPP. 2014. Technical Specifications Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) Radio Transmission and reception (Release 12) - 3GPP TS 36.101 V12.5.0. Report, 3GPP.
- FCC. 2014. Amendment of the Commission's Rules with Regard to Commercial Operations in the 1695-1710 MHz, 1755-1780 MHz, and 2155-2180 MHz Bands. Report and Order, Washington: FCC.
- FCC. 2003. Service Rules for Advanced Wireless Services in the 1.7 GHz and 2.1 GHz Bands. Report and Order, Washington: FCC.
- GSA. 2017. "Status of the LTE Ecosystem." *LTE Status of the LTE Ecosystem Report GSA*. 5 April. Accessed 2017. https://gsacom.com/paper/status-lte-ecosystem-report-gsa/.
- GSMA. 2016. "4G Market and Technology Update." LTE GSA: Evolution to LTE October 2016. 26 October. Accessed July 5, 2017. https://gsacom.com/paper/gsa-evolution-lteoctober-2016/.
- GSMA. 2014. *Global Perspectives. GSMA presentation at the Ericsson conference on APT 700.* 5 March.
- GSMA. 2014. Status of the LTE Ecosystem. Report, GSA.
- ITU. 2015. Handbook on National Spectrum Management. Geneva: ITU-R.
- —. 2017. *ITU agrees on key 5G performance requirements for IMT-2020.* 23 February. https://www.itu.int/en/mediacentre/Pages/2017-PR04.aspx.
- ITU. 2022. Meeting Report WP 5D #41. Geneva, June.
- —. 2022. WRS-22: Mobile broadband trends from 3G to 6G. 6 December. Accessed December 22, 2022. https://www.itu.int/hub/2022/12/wrs-22-mobile-broadband-trends-from-3g-to-6g/.
- ITU-R. 2010. "Definitions of World Telecommunication/ICT Indicators." https://www.itu.int/ITU-D/ict/material/TelecomICT Indicators Definition March2010 for web.pdf.
- ITU-R. 2020. Radio Regulations Articles Edition of 2020. Geneva.
- —. 2012. "Radio Regulations: Articles." Accessed October 20, 2016. http://www.itu.int/dms_pub/itu-s/oth/02/02/S02020000244501PDFE.PDF.

- TATT. 2008. *National Spectrum Plan*. Plan, Port of Spain: Telecommunications Authority of Trinidad and Tobago.
- TATT. 2021. Procedures for Consultation in the Telecommunications and Broadcasting Sectors of Trinidad and Tobago. Procedures, Port of Spain: Telecommunications Authority of Trinidad and Tobago.